

### Counterweight Dimensions

Counterweight No.	1	2	3	4	5	6	7	8	9
<b>A</b>	49.25	47.25	43.25	43.25	43.25	39.375	35.5	29.5	25.5
<b>B</b>	66.875	66.875	59.0625	59.0625	55.125	49.1875	45.25	39.375	31.5
<b>C</b>	9.5	7.875	8	7.25	6.75	6.75	5.875	5.875	5.875
<b>D</b>	18.5	17.75	16.75	16.75	16.75	15	14	11.5	10
<b>E</b>	11.875	11.875	11.875	10.5	8.875	8.875	6.875	6.875	6.875
<b>F</b>	19.75	19.75	17.75	17.75	15.75	15.75	15.75	13.75	14.625
<b>G</b>	23.625	23.625	23.625	23.625	23.625	19.625	19.625	15.75	9.625
<b>H</b>	23.625	23.625	23.625	23.625	23.625	19.625	19.625	7.875	9.125
<b>I</b>	5.5	5.5	5.5	5.5	5.5	5.5	5.5	5.5	5.25
<b>R</b>	102.375	102.375	102.375	94.5	76.875	76.875	66.325	66.375	54
<b>Weight/ea, lbs</b>									
2H, 2 bolt holes						2200	1650	1215	850
3H, 3 bolt holes	5280	4211	3582	3247	2622				

weights in lbs. & dimensions in inches

