

<b>LS Unit Model</b>	<b>C160D-143-74</b>			
		<b>ECB, lbs.</b>	<b>ECB, lbs.</b>	<b>ECB, lbs.</b>
<b>Qty of Cwts</b>	<b>Cwt position * on crank arm</b>	<b>@74" stroke, at position</b>	<b>@64" stroke, at position</b>	<b>@53" stroke, at position</b>
<b>Counterweight No.:</b>	<b>7 (2 bolts)</b>			
cranks only		3,219	3,623	4,198
4	10	5,088	5,788	6,782
4	20	6,957	7,953	9,367
4	30	8,826	10,118	11,952
4	40	10,695	12,283	14,537
4	max 45.4	11,704	13,453	15,933
2	10	4,154	4,706	5,490
2	20	5,088	5,788	6,782
2	30	6,023	6,871	8,075
2	40	6,957	7,953	9,367
2	max 45.4	7,462	8,538	10,065
<b>Counterweight No.:</b>	<b>8 (2 bolts)</b>			
cranks only		3,219	3,623	4,198
4	10	4,465	5,067	5,921
4	20	5,711	6,510	7,644
4	30	6,957	7,953	9,367
4	40	8,203	9,397	11,090
4	max 55.4	9,312	10,681	12,624
2	10	3,842	4,345	5,059
2	20	4,465	5,067	5,921
2	30	5,088	5,788	6,782
2	40	5,711	6,510	7,644
2	max 55.4	6,266	7,152	8,411