

LS Unit Model	C160D-173-74			
		ECB, lbs.	ECB, lbs.	ECB, lbs.
Qty of Cwts	Cwt position * on crank arm	@74" stroke, at position	@64" stroke, at position	@53" stroke, at position
Counterweight No.:	7 (2 bolts)			
cranks only		3,219	3,623	4,198
4	10	5,088	5,788	6,782
4	20	6,957	7,953	9,367
4	30	8,826	10,118	11,952
4	40	10,695	12,283	14,537
4	max 45.4	11,704	13,453	15,933
2	10	4,154	4,706	5,490
2	20	5,088	5,788	6,782
2	30	6,023	6,871	8,075
2	40	6,957	7,953	9,367
2	max 45.4	7,462	8,538	10,065
Counterweight No.:	8 (2 bolts)			
cranks only		3,219	3,623	4,198
4	10	4,465	5,067	5,921
4	20	5,711	6,510	7,644
4	30	6,957	7,953	9,367
4	40	8,203	9,397	11,090
4	max 48.9	9,312	10,681	12,624
2	10	3,842	4,345	5,059
2	20	4,465	5,067	5,921
2	30	5,088	5,788	6,782
2	40	5,711	6,510	7,644
2	max 48.9	6,266	7,152	8,411